



"Simple, Reliable, and Effective Flow Control"

The Sliding Gate is designed to control or completely shut off the flow of bulk materials in conveying lines, silos, and bins. Its smooth sliding mechanism allows operators to adjust product flow accurately, supporting stable and efficient material handling processes.

Sürgü Klappe Sliding Gate Ручной Шибберный Затвор



High Performance

Высокая
производительность



Less Energy

Меньше
Энергии



Maximum Capacity

Максимальная
емкость

Type Model	KRM-SG 170	KRM-SG 200	KRM-SG 250	KRM-SG 270	KRM-SG 320
Ağırlık (Brüt)	10 KG	13 KG	14 KG	17 KG	19 KG
Toplam Uzunluk	556 mm	610 mm	650 mm	750 mm	850 mm
Teknik Özellikler	Direk Bağlantı	Direk Bağlantı	Direk Bağlantı	Direk Bağlantı	Direk Bağlantı
Motor Gücü	Kullanılmıyor 40/170 mm Kullanılmıyor 40/170 mm	Kullanılmıyor 40/200 mm Kullanılmıyor 40/200 mm	Kullanılmıyor 40/250 mm Kullanılmıyor 40/250 mm	Kullanılmıyor 40/270 mm Kullanılmıyor 40/270 mm	Kullanılmıyor 40/320 mm Kullanılmıyor 40/320 mm
Voltaj Frekans	380 volt - 50 hertz	380 volt - 50 hertz	380 volt - 50 hertz	380 volt - 50 hertz	380 volt - 50 hertz
Ekipman	Karbon Çelik ST37	Karbon Çelik ST37	Karbon Çelik ST38	Karbon Çelik ST38	Karbon Çelik ST37
Yüzey	Boyalı	Boyalı	Boyalı	Boyalı	Boyalı