



"Airlock Precision for Efficient Material Flow"

The Ecluse is designed to regulate the flow of powdered or granular materials between different pressure zones. It allows product to pass through while maintaining an airtight seal, ensuring stable discharge and preventing unwanted air infiltration into the system.

Eklüs
Ecluse
Эклюс



High Performance

Высокая
производительность



Less Energy

Меньше
Энергии



Maximum Capacity

Максимальная
емкость

Type Model	KRM-EC 250	KRM-EC 320	KRM-EC 470
Ağırlık (Brüt)	199 KG	320 KG	331 KG
Kapasite (Buğday)	9,5 Ton/Saat	18 Ton/Saat	60 Ton/Saat
Kapasite (Un - İrmik)	5,5 Ton/Saat	12,5 Ton/Saat	38 Ton/Saat
Kapasite (Kepek)	3.0 Ton/Saat	6,5 Ton/Saat	21 Ton/Saat
Teknik Özellikler	Rotor Çapı Ø250	Rotor Çapı Ø315	Rotor Çapı Ø420
Motor Gücü	0,55 kw	0,75 kw	1,1 kw
Voltaj Frekans	380 volt 50 hertz	380 volt 50 hertz	380 volt 50 hertz
Ekipman	Karbon Çelik ST37	Karbon Çelik ST37	Karbon Çelik ST37
Yüzey	Boyalı	Boyalı	Boyalı