

Hava Kilidi

Air Lock

Шлюзовой Затвор



High Performance

Высокая производительность



Less Energy

Меньше Энергии



Maximum Capacity

Максимальная емкость

“Seamless Material Transfer with Perfect Air Sealing”

The Air Lock is designed to transfer bulk materials between different pressure zones without air leakage. By maintaining an airtight seal, it protects system pressure stability, enhances the performance of pneumatic conveying and dust collection systems, and prevents material backflow.



Type Model	KRM-AL 220	KRM-AL 240	KRM-AL 300
Ağırlık (Brüt)	81 KG	88 KG	104 KG
Kapasite (Buğday)	8,2 Ton/Saat	10,5 Ton/Saat	13,2 Ton/Saat
Kapasite (Un - İrmik)	5,8 Ton/Saat	7,5 Ton/Saat	9,4 Ton/Saat
Kapasite (Kepek)	3,2 Ton/Saat	4,1 Ton/Saat	5,2 Ton/Saat
Toplam Uzunluk	Ø220 mm	Ø240 mm	Ø300 mm
Teknik Özellikler	Brüt Hacim 0,1 m³	Brüt Hacim 0,1 m³	Brüt Hacim 0,1 m³
Motor Gücü	0,55-0,75 kw 45 rpm.	0,55-0,75 kw 45 rpm.	0,55-0,75 kw 45 rpm.
Voltaj Frekans	380 volt 50 hertz	380 volt 50 hertz	380 volt 50 hertz
Ekipman	Karbon Çelik ST37	Karbon Çelik ST37	Karbon Çelik ST37
Yüzey	Boyalı	Boyalı	Boyalı